

JC930 U.S. PTO
10/19/00

10-20-00

PATENT

Attorney Docket No. GSMITH.002A

Date: October 19, 2000

Page 1

ASSISTANT COMMISSIONER FOR PATENTS

WASHINGTON, D.C. 20231

ATTENTION: BOX PATENT APPLICATION

Sir:

Transmitted herewith for filing is the patent application of

Inventor(s): **Gary Smith**

For: **ROOF TILE SUPPORT**

Enclosed are:


- (X) Seven (7) sheets of drawing.
- (X) Return prepaid postcard.

JC922 U.S. PTO
09/692655
10/19/00

CLAIMS AS FILED

| FOR | NUMBER FILED | NUMBER EXTRA | RATE | FEE |
|--------------------------------------------------------------------|-----------------|-----------------|-------|----------|
| Basic Fee | | | \$355 | \$355.00 |
| Total Claims | 28 - 20 = | 8 × | \$9 | \$72.00 |
| Independent Claims | 3 - 3 = | 0 × | \$40 | \$ 0.00 |
| If application contains any multiple dependent claims(s), then add | | | \$135 | \$N/A |
| FILING FEE TO BE PAID AT A LATER DATE | | | | \$427.00 |

- (X) Please use Customer No. 20,995 for the correspondence address.


William B. Bunker
Registration No. 29,365
Attorney of Record

H:\DOCS\WBB\WBB-1867.DOC
101200

KNOBBE, MARTENS, OLSON & BEAR

A LIMITED LIABILITY PARTNERSHIP INCLUDING
PROFESSIONAL CORPORATIONS

PATENT, TRADEMARK AND COPYRIGHT CAUSES

620 NEWPORT CENTER DRIVE

SIXTEENTH FLOOR

NEWPORT BEACH, CALIFORNIA 92660-8016

(949) 760-0404

FAX (949) 760-9502

INTERNET WWW.KNOB.COM

LOUIS J. KNOBBE*
DON W. MARTENS*
GORDON H. OLSON*
JAMES B. BEAR
DARRELL L. OLSON*
WILLIAM B. BUNKER
WILLIAM H. NIEMAN
ARTHUR S. ROSE
JAMES F. LESNIAK
NED A. ISRAELSEN
DREW S. HAMILTON
JERRY T. SEWELL
JOHN B. SGANGA, JR.
EDWARD A. SCHLATTER
GERARD VON HOFFMANN
JOSEPH R. RE
CATHERINE J. HOLLAND
JOHN M. CARSON
KAREN VOGEL WEIL
ANDREW H. SIMPSON
JEFFREY L. VAN HOUSEAR
DANIEL E. ALTMAN
MARGUERITE L. GUNN
STEPHEN C. JENSEN
VITO A. CANUSO III
WILLIAM H. SHREVE
LYNDA J. ZADRA-SYMES†
STEVEN J. NATAUPSKY
PAUL A. STEWART
JOSEPH F. JENNINGS
CRAIG S. SUMMERS
ANNEMARIE KAISER
BRENTON R. BABCOCK

THOMAS F. SMERAL, JR.
MICHAEL H. TRENHOLM
DIANE M. REED
JONATHAN A. BARNEY
RONALD J. SCHOENBAUM
JOHN R. KING
FREDERICK S. BERRETTA
NANCY WAYS VENSKO
JOHN P. GIEZENTANNER
ADEEL S. AKHTAR
GINGER R. DREGER
THOMAS R. ARNO
DAVID N. WEISS
DANIEL HART, PH.D.
DOUGLAS G. MUEHLHAUSER
LORI LEE YAMATO
MICHAEL K. FRIEDLAND
STEPHEN M. LOBBIN
STACEY R. HALPERN
DALE C. HUNT, PH.D.
LEE W. HENDERSON, PH.D.
DEBORAH S. SHEPHERD
RICHARD E. CAMPBELL
MARK M. ABUMERI
JON W. GURKA
ERIC M. NELSON
MARK R. BENEDICT, PH.D.
PAUL N. CONOVER
ROBERT J. ROBY
SABING H. LEE
KAROLINE A. DELANEY
JOHN W. HOLCOMB
JAMES J. MULLEN, III, PH.D.

JOSEPH S. CIANFRANI
JOSEPH M. REISMAN, PH.D.
WILLIAM R. ZIMMERMAN
GLEN L. NUTTALL
ERIC S. FURMAN, PH.D.
TIRZAH ABE LOWE
GEOFFREY Y. HIOA
ALEXANDER S. FRANCO
SANJIVPAL S. GILL
SUSAN M. MOSS
JAMES W. HILL, M.D.
ROSE M. THIESSEN, PH.D.
MICHAEL L. FULLER
MICHAEL A. GUILIANA
MARK J. KERTZ
RABINDER N. NARULA
BRUCE S. ITCHKAWITZ, PH.D.
PETER M. MIDDLEY
THOMAS S. MCCLENAHAN
MICHAEL S. OKAMOTO
JOHN M. GROVER
MALLARY K. DE MERLIER
IRFAN A. LATEEF
AMY C. CHRISTENSEN
SHARON S. NG
MARK J. GALLAGHER, PH.D.
DAVID G. JANKOWSKI, PH.D.
BRIAN C. HORNE
PAYSON J. LEWILLEUR
WILLIAM G. BERRY
DIANA W. PRINCE

OF COUNSEL

JERRY R. SEILER
PAUL C. STEINHARDT

JAPANESE PATENT ATTY
KATSUHIRO ARAI**

EUROPEAN PATENT ATTY
MARTIN HELLEBRANDT

KOREAN PATENT ATTY
MINCHEOL KIM

SCIENTISTS & ENGINEERS
(NON-LAWYERS)

RAIMOND J. SALENIEKS**
DANIEL E. JOHNSON, PH.D.**
JEFFERY KOEPKE, PH.D.**
KHURRAM RAHMAN, PH.D.
JENNIFER A. HAYNES, PH.D.
BRENDAN P. O'NEILL, PH.D.
THOMAS Y. NAGATA
LINDA H. LIU
YASHWANT VAISHNAV, PH.D.
MEGUMI TANAKA
CHE S. CHERESKIN, PH.D.**
ERIK W. ARCHBOLD
PHILIP C. HARTSTEIN
JULIE A. HOPPER
CHRIS S. CASTLE
JAMES W. AUSLEY
R. P. CARON, PH.D.
JENNIFER HAYES
KIRK E. PASTORIAN, PH.D.
CHARLES T. RIDGELY
KEITH R. MCCOLLUM
LANG J. MCHARDY

* A PROFESSIONAL CORPORATION
† ALSO BARRISTER AT LAW (U.K.)
** U.S. PATENT AGENT

Assistant Commissioner for Patents
Washington, D.C. 20231


CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Attorney Docket No. : GSMITH.002A
Applicant(s) : GARY SMITH
For : ROOF TILE SUPPORT
Attorney : William B. Bunker
"Express Mail"
Mailing Label No. : EL512369896US
Date of Deposit : October 19, 2000

I hereby certify that the accompanying

Transmittal in Duplicate; Specification in 15 pages; 7 sheets of drawings; Return
Prepaid Postcard

are being deposited with the United States Postal Service "Express Mail Post Office to
Addressee" service under 37 CFR 1.10 on the date indicated above and are addressed to the
Assistant Commissioner for Patents, Washington, D.C. 20231.


Justin Stotts

H:\DOCS\WBB\WBB-1875.DOC\101900

JC922 U.S. PTO
09/692655
10/19/00

ROOF TILE SUPPORTBackground of the Invention5 Field of the Invention

The present invention relates generally to roofing products, and more specifically, to a roof tile support that allows individuals to walk on a tile roof without breaking tiles.

Description of the Related Art

10 Tile is one of the predominant roofing products in use today because of its many advantages over other roofing systems. Tile has a long life span and provides good weather resistance. A tile roof requires little maintenance and is not subject to rotting or insect damage. Tile is fire safe and is available in many different colors, shapes, and styles. Additionally, cement or concrete tiles are generally lighter and cost less than
15 traditional clay or ceramic tiles and can be used on most roofs without having to provide structural reinforcements for the roof.

One of the only disadvantages of a tile roof is that it is difficult to walk on it without breaking tiles. Sometimes it is necessary to walk on a roof to paint the trim, clean windows or gutters, and remove foreign objects. Tile roofs generally cannot take
20 heavy traffic. Careless foot placement or just "heavy feet" can result in broken tiles. Tile is usually placed on a roof with one side secured to the roofing surface, and the other side resting on, and overlapping, another tile. This overlapping creates a space or gap beneath each tile. Stepping on the middle of a tile will likely break it because the tile is not well supported in that location.

25 Usually only professional roofers are able to walk on tile roofs without damaging any tiles. Yet even a professional tile installer must take great care not to break pieces while walking over the tiles. When walking on a roof, professionals have to choose a route carefully across the reinforced and supported section of each tile. They must walk on the butt of the tile where it rests on solid material, usually at the
30 point where one tile overlaps the next. They must avoid stepping in the center of the

tiles where the tiles are vulnerable to fracture. They must focus on distributing their weight evenly between both feet, and walking slowly and softly.

Some tile manufacturers have attempted to improve the "walkability" of their tiles by adding a small post on the underside of the tile that provides support for when someone steps on the middle of the tile. There are several problems with this approach. First, because the posts are an integral part of the tile and consist of the same brittle material as the tiles, they often break off during delivery, installation, or use. Second, the tiles cannot be packaged as compactly and the volume that the tiles occupy during delivery is doubled, leading to increased shipping and delivery costs.

Additionally, tile is laid according to the specific design of an individual roof. Roofers often vary the amount that each row of tiles overlaps the next row in order to cover the roofing surface with uniform rows of tile. A third problem with the posts is that the amount of overlap, or head lap, for those tiles should not be adjusted. By moving a tile forward to increase the head lap, the post does not reach the roofing surface and the tile will rest too low. In this condition, the post is not supporting the tile and the tile is likely to fracture when stepped on. By moving the tile backward to decrease the head lap, the post will be supported higher up on the roof causing the tile to rest too high. In this condition, the post is likely to snap off under a person's weight and the tile is just as likely to break as if there were no post at all.

Some tile manufacturers have introduced different support structures that are permanently attached to their tiles. The biggest problem with these tile structures is their lack of flexibility. As mentioned above, roofers need to be able to adjust the head lap of the tiles to conform to the dimensions and shapes of custom roofs. These pre-supported tile structures require precise alignment and cannot be easily modified by the installer to fit the shape of the roof. Additionally these tile structures are sometimes expensive and are not available in as many colors and styles as the individual roof tiles.

Summary of the Invention

The present invention recognizes the desirability of being able to walk on a tile roof with confidence that the tiles will not break. The present invention satisfies the need for a roof tile support element that is compatible with a broad range of roof tiles, is

adjustable during installation, and that allows individuals to walk confidently on a tile roof without breaking tiles.

5 In one embodiment of the present invention, a support element fits between roof tiles and a roofing surface to provide support for the roof tiles. Preferred embodiments of the present invention further include roof tile support systems and methods for installing roof tile supports.

10 In one embodiment of the present invention, a support element is preferably wedge-shaped to correspond to the space between the tiles and the roofing surface and to provide support under as much of the tile as possible. The wedge-shaped support element is preferably made of expanded polystyrene so that it is lightweight, durable, semi-compressible, fire safe, inexpensive and easy to manufacture and install. Roof tiles placed on the wedge-shaped support element are preferably supported by the support element, and rest on the back end portion of the next lower course of tiles. This allows downward forces acting on a tile to be distributed over the tile and through the support element to the roofing surface. This distribution of the forces prevents the tile from breaking.

15 Support elements are preferably independent of the roof tiles. Individual support elements can be mass-produced for use with different, but similar, kinds of tile. Additionally, during installation the roof tiles can be adjusted forward or backward with respect to the support element in order to increase or decrease the head lap of the tiles. Support elements that are not attached to tiles are more cost effective in terms of packaging and delivery than combined structures.

20 Another preferred embodiment of the invention is a roof tile support system with a roofing surface, roof tiles, and support elements. The support elements are preferably positioned between the roofing surface and the tiles in a manner suitable for distributing and transferring concentrated forces acting on the tiles more evenly to the roofing surface. Distributing and transferring the forces increases the load capacities of the tiles and improves the walkability of the roof.

25 One of the preferred methods for installing roof tile supports comprises placing a support element on a roofing surface, placing a roof tile over the support element, and securing the roof tile to the roofing surface.

Brief Description of the Drawings

FIGURE 1 is a perspective view, partly in cross-section, of a roof tile support system illustrating one embodiment of the present invention;

5 **FIGURE 2** is a perspective view of a portion of the roof tile support system of **FIGURE 1**;

FIGURE 3 is a perspective view, partly in cross-section, of another embodiment of a roof tile support system;

FIGURE 4 is a perspective view of a roof tile support element according to one embodiment of the present invention;

10 **FIGURE 5** is a perspective view of another embodiment of a roof tile support element;

FIGURE 6 is a perspective view in cutaway of an alternative embodiment of a roof tile support element for the roof tile of figure 3.

15 **FIGURE 7** is a perspective view of a packaging assembly illustrating a method of packaging a plurality of roof tile support elements.

Detailed Description of the Preferred Embodiment

One embodiment of the invention is illustrated in **FIGURE 1**, in which a roof tile support system 10 is shown covering a portion of a roof. A roofing surface 12 is shown. Several roof tile support elements 14 are shown resting on the roofing surface 12. Finally, several roof tiles 16 are shown resting on the roof tile support elements 14 and the roofing surface 12.

20 Preferably, the roofing surface 12 is a structure capable of receiving and supporting a tile roof. In a preferred embodiment of the invention, the roofing surface 12 is a supported plywood deck 18 covered by tarpaper 20. In other embodiments of the invention, the roofing surface 12 also includes battens to which roof tiles 16 are attached. In the preferred embodiment of **FIGURE 1**, one end of the roofing surface 12 has a wooden cross member 22 to which the eave metal 24a,b of the roof is attached. One skilled in the art will be familiar with other variations or combinations of materials constituting a roofing surface 12.

30 In a preferred embodiment of the invention, a roof tile support element 14 fits between roof tiles 16 and a roofing surface 12 to provide support for the roof tiles 16.

Preferably, a support element 14 is wedge-shaped to correspond to the space between the tiles 16 and the roofing surface 12 and to provide support under as much of the tile 16 as possible. The support element 14 is preferably made of expanded polystyrene so that it is lightweight, durable, semi-compressible, fire safe, inexpensive and easy to manufacture and install. Alternatively, the support element 14 may be made of other materials such as foam, rubber, plastic, or any other material which provides sufficient support when used as described herein.

The support element 14 preferably rests directly on the roofing surface 12. Support elements 14 are preferably arranged in rows on the roofing surface 12. A support element 14 in a row is preferably one or two inches away 26 from the next support element 14 in the row. The space 26 between the support elements 14 is preferred to facilitate water drainage on the roof.

In a preferred embodiment of the invention a roof tile 16 is a roof-covering product that is brittle, subject to fracture, or likely to break under the weight of an individual walking on an installed roof. In a particular preferred embodiment illustrated in **FIGURE 1**, the roof tile 16 is a lightweight concrete tile in a shake or slate profile. The roof tile 16 has a back end portion 28 which is preferably supported by the thinner end of the support element 14 such that it does not contact the roofing surface 12, thereby "floating" the roof tile 16 above the roof surface 12. A middle portion 30 of the roof tile 16 preferably rests on the support element 14. A front end portion 32 of the roof tile 16 overlaps the back end portions 28 of the tiles 16 of the next lower course. In this configuration, each roof tile 16 effectively floats on the support element 14. This allows for loads to be evenly distributed across the tiles 16, support elements 14, and roof surface 12 respectively.

In an alternative embodiment, the support element 14 may have a triangular cross-section as illustrated in **FIGURES 3 and 4**. In this embodiment, the roof tile 16 may be positioned on the support element 14 such that the back end portion 28 rests on the roofing surface 12. In this particular embodiment, the roofing tile is partly supported by the roofing surface 12 as well as by the support element 14.

In a preferred embodiment shown in **FIGURE 2**, roof tiles 16 placed on the wedge-shaped support element 14 preferably rest on the next lower course of tiles 16.

This allows downward forces acting on a tile 16 to be distributed over the tile 16 and through the support element 14 to the roofing surface 12. This distribution of the forces prevents the tile 16 from breaking. Preferably, roof tiles 16 placed on the support elements 14 will rest directly on the next lower course of tiles 16.

5 The roof tiles 16 are preferably secured in place using nails 36 appropriate for use with roof tiles 16. As illustrated in **FIGURE 2**, the nails 36 may pass through both the roof tile 16 and the support element 14. In other embodiments, the nails 36 may only pass through the roof tiles 16. Support elements 14 are preferably independent of the roof tiles 16. During installation, roof tiles 16 can be adjusted forward or backward
10 with respect an independent support element 14 in order to increase or decrease the amount of overlap 38 of the tiles 16.

 Another preferred embodiment of the invention is illustrated in **FIGURE 3**, in which a roof tile support system 10 is shown covering a portion of a roof. A roofing surface 12 is shown comprising a roof deck 18 and a layer of tarpaper 20. One end of
15 the roofing surface 12 has a wooden cross member 22 to which the eave metal 24a of the roof is attached. Several wedge-shaped roof tile support elements 14 are shown resting on the roofing surface 12. Finally, a roof tile 16 is shown resting on a roof tile support element 14.

 In a particular preferred embodiment illustrated in **FIGURE 3**, the roof tile 16 is
20 a lightweight concrete tile in a barrel profile. The roof tile 16 has a back end portion 28 that preferably rests on the support element 14. A middle portion 30 of the roof tile 16 preferably rests on the support element 14 as well. A front end portion 32 of the roof tile 16 is shown overhanging the edge of the roof. Generally, in higher rows, the front end portion 32 of a roof tile 16 preferably overlaps the back end portions 28 of the tiles
25 16 of the next lower course.

 The barrel roof tiles 16 that are placed on the wedge-shaped support elements 14 are preferably supported by the support elements 14, but rest directly on the next lower course of tiles 16. Preferably, roof tiles 16 placed on the support elements 14 will rest on the back end portion 28 of the next lower course of tiles 16.

30 In another preferred embodiment, as shown in **FIGURE 6**, the support element 14 has arched sections 72 corresponding to the barrel sections 70 of the roof tiles. The

arch sections 72 may be integrally formed with the rest of the support element 14 such that a shape similar to the underside of the barrel roof tile 16 is created. Alternatively, the arch sections 72 may be separate or detachable from the rest of the support element 14, in which case the arch sections 72 may be held in place by glue, tape, or simply by friction. **FIGURE 6** shows the support element with a triangular cross-section, however, a support element having features and advantages of the present invention may also have a quadrilateral cross-section in combination with the arch sections 72 described above.

One embodiment of the invention, shown in **FIGURE 4**, is a roof tile support element 14. Support elements 14 are preferably independent of roof tiles. Individual support elements 14 can be mass-produced for use with different, but similar, kinds of tile. The support element 14 is preferably made of expanded polystyrene. The support elements 14 are preferably cut from a large block of expanded polystyrene with a hot wire.

In a particular preferred embodiment shown, the support element 14 is wedge-shaped. The wedge-shaped support element 14 has a triangular cross-section 40. The support element preferably has a top surface 56 for contacting roof tiles and a bottom surface 58 for contacting a roofing surface. Preferably, the large surface areas on the top and bottom of the support element are in contact with substantial portions of the roof tiles and the roofing surface. The support element 14 is preferably long enough to support between three and five roof tiles. Other embodiments, however, may support more or fewer tiles. The support element 14 is preferably four feet long 42.

The width 44 and the height 46 of the support element 14 will vary depending on the specific shape and size of the roof tiles with which the support element is designed to be compatible. Preferably, the height 46 at the front end 48 of the support element 14 will be about 0.125" higher than the height of the back end portion of a roof tile on the next lower course. The width 44 of the support element 14 is preferably wide enough that its bottom surface 58 covers a majority of the roofing surface directly below the middle portions of corresponding roof tiles. The width 44 of the support element 14 is preferably wide enough that its top surface 56 contacts a majority of the surface under the middle portions of corresponding roof tiles.

For example, a roof tile support element 14, with a triangular cross section 40, may be designed to be compatible with roof tiles that are approximately 15" long, 12" wide and 1" tall. The front end portion of the roof tile may be intended to overlap a lower course of tiles by about 3" with the back end portion of the tile intended to be in contact with a roofing surface for about 1". The front end portion of the roof tile may be supported above the back end portion next lower course of roof tiles. The distance that a roof tile 16 (FIGURE 1) should be supported above the next lower course of tiles 16 (FIGURE 1) is related to the compressibility of the support element 14. When someone walks on the tile roof supported by support elements 14 with a triangular cross section, the support element 14 will be compressed and the distance between the upper and lower tiles 16 will decrease.

A roof tile support element 14 designed to be compatible with such a tile could be four feet long 42, 11" wide 44, and 1.125" tall 46. In such an arrangement, four tiles could be placed over the support element 14. The bottom surface of the support element 14 would be covering a majority of the roofing surface directly below the middle portions of the four roof tiles. The middle portions of the lower surfaces of the four roof tiles would be in contact with the top surface 56 of the support element 14. A majority of the surface area under the roof tile, that is not overlapping lower tiles or in contact with the roofing surface, would be supported by the support element 14.

Other embodiments of the support element 14 may effectively support roof tiles by contacting less than a majority of the surface under the middle of the tiles. Some tiles with barrel profiles, for example, may be supported sufficiently even though the top surface of the support element may not contact a majority of the bottom surface of the middle of the tiles. Preferably, support elements contact and support roof tiles at selected locations on the underside of the tiles to generally provide support to the otherwise unsupported middle sections of the tiles.

In a similar preferred embodiment shown in **FIGURE 5**, the support element 14 is again wedge-shaped. However, the wedge-shaped support element 14 has a quadrilateral cross-section 50 rather than a triangular cross-section. The support element preferably has a thicker front end 48 and a thinner back end 60. The support element preferably has a top surface 56 for contacting roof tiles and a bottom surface 58

for contacting a roofing surface. Preferably, the large surface areas on the top and bottom of the support element are in contact with substantial portions of the roof tiles and the roofing surface.

5 A support element with a quadrilateral cross-section 50 may be preferable with certain shapes, sizes or types of tiles. In one preferred embodiment, the support element 14 is compatible with roof tiles requiring battens on the roofing surface. In other embodiments the support element 14 is compatible with roof tiles which may or may not require battens.

10 The thinner back end 60 of a support element 14 can be placed adjacent to a batten. The height 62 of the thinner back end 60 of the support element 14 is preferably the same height or slightly higher than the batten. Preferably, the height 46 at the thicker front end 48 of the support element 14 will be about the same as the height of the back end portion of the roof tile and batten of the next lower course.

15 The width 44 of the support element 14 is preferably wide enough for the bottom surface 58 of the support element to contact and cover a majority of the roofing surface under the middle portions of the corresponding roof tiles. Additionally, the width 44 of the support element 14 is also preferably wide enough that its top surface 56 contacts a majority of the surface under the middle portions of corresponding roof tiles. However, as noted previously, other embodiments may effectively support the tiles by contacting
20 less than a majority of the surface under the middle of the tiles.

In one specific preferred embodiment, a support element 14 is compatible with an Eaglelite Malibu tile to be installed on a roofing surface with battens. The support element 14 for use with this type of tile is four feet long 42 and 11" wide 44. The height 46 of the thicker front end 48 is 1.875" and the height 62 of the thinner back end
25 60 is 1".

In another preferred embodiment, a support element 14 is compatible with a Monier Cedarlite tile. The support element 14 for use with this type of tile is four feet long 42 and 7.5" wide 44. The height 46 of the thicker front end 48 is 1" and the height 62 of the thinner back end 60 is 0.375". One skilled in the art will be familiar with
30 these manufacturers and tiles.

FIGURE 7 illustrates a preferred packaging assembly 52 of roof tile support elements 14. A number of support elements 14 are shown arranged into a bundle 52. The support elements 14 are preferably stacked in an alternating fashion such that each overlaying element 14 is turned 180° relative to the adjacent elements 14 stacked thereby. The support elements 14 are preferably bound with a plastic wrap 54 or some other method of binding. In another preferred embodiment the support elements 14 are packaged in bags. Support elements 14 that are independent of roof tiles are more cost effective in terms of packaging and delivery than combined structures.

A preferred method of installing roof tile supports, comprises placing a support element on a roofing surface, placing a roof tile over a support element, and securing the roof tile to the roofing surface. Embodiments of the invention vary depending on the type of support elements and roof tiles used. In one preferred method, as seen in **FIGURE 3**, the roof tile 16 is placed so that it is in contact with, and rests completely on, the support element 14. In another embodiment, an example of which is shown in **FIGURE 1**, the roof tile 16 is placed so that it rests on the support element 14 and the roofing surface 12. In another method, the roof tile 16 may be placed so that it rests on a support element 14 and the tiles 16 of the next lower course. In still another embodiment, the roof tile 16 may be placed so that it rests on the roofing surface 12, the support element 14, and the tiles 16 of the next lower course.

Preferably, the roof tiles 16 are placed over the support elements 14 and then secured to the roofing surface using roofing nails 36, such as shown in **FIGURE 1**. In a preferred method of installation the nail 36 passes through both the roof tile 16 and the support element 14 and into the roofing surface 12 to secure the tile 16. In another preferred method, the nail 36 passes through the tile 16 and into the roofing surface 12 and the weight of the tile 16 acts to secure the support element 14. One preferred method of installing roof tile supports 14 includes positioning a second support element 14 in a row next to a first support element 14, leaving a gap 26 between the two elements 14 to facilitate water drainage on the roof. Alternatively, water drainage may be further facilitated by forming grooves 13 in the bottom surface of the support elements 14, e.g. the surface which contacts the roofing surface 12. Such grooves 13 would allow water to flow underneath each support element 14 as well as between them.

[illegible]

WHAT IS CLAIMED IS:

1. An apparatus adapted for use with roof tiles and a roofing surface, comprising a support element configured to occupy the space between roof tiles and a roofing surface thereby providing support for the roof tiles.

5 2. The apparatus of Claim 1, wherein said support element is configured in the shape of a wedge.

3. The apparatus of Claim 2, wherein said support element has a triangular cross-section.

10 4. The apparatus of Claim 2, wherein said support element has a quadrilateral cross-section.

5. The apparatus of Claim 1, wherein said support element is made of expanded polystyrene.

6. The apparatus of Claim 1, wherein said support element includes at least one groove formed in its bottom surface.

15 7. The apparatus of Claim 2, further comprising arch sections.

8. A roof tile support system, comprising:

a roofing surface;

one or more roof tiles; and

20 one or more independent support elements positioned between said roofing surface and said roof tiles, wherein said support elements support said roof tiles so as to increase the load capacities of said roof tiles.

9. The roof tile support system of Claim 8, wherein said roofing surface comprises a roof deck.

25 10. The roof tile support system of Claim 8, wherein said roofing surface comprises a roof deck with battens.

11. The roof tile support system of Claim 8, wherein said roof tiles are made of lightweight concrete.

12. The roof tile support system of Claim 8, wherein said support elements are separate pieces from said roof tiles and said roofing surface.

30 13. The roof tile support system of Claim 8, wherein each of said support elements supports a plurality of roof tiles.

14. The roof tile support system of Claim 8, wherein said support elements have a large surface area for contacting a substantial portion of the area under said roof tiles.

5 15. The roof tile support system of Claim 8, wherein said support elements are wedge-shaped.

16. The roof tile support system of Claim 15, wherein said support elements have arch sections, and said roof tiles are barrel roof tiles.

17. The roof tile support system of Claim 15, wherein said support elements have a triangular cross-section.

10 18. The roof tile support system of Claim 15, wherein said support elements have a quadrilateral cross-section.

19. The roof tile support system of Claim 8, wherein said support elements are made of expanded polystyrene.

15 20. The roof tile support system of Claim 8, wherein said roof tiles are arranged in rows and a first row is supported by said support elements such that the roof tiles of the first row are elevated some distance above a second adjacent row of said roof tiles.

20 21. The roof tile support system of Claim 8, wherein said roof tiles are supported by said support elements such that the weight of said tiles, or a concentrated load on said tiles, will be distributed over said support elements and said roofing surface.

25 22. The roof tile support system of Claim 8, wherein said roof tiles are arranged in rows and a first row is supported by said support elements such that the weight of said tiles, or a concentrated load on said tiles, will be distributed over said support elements, said roofing surface and a second row of roof tiles.

23. A method of installing roof tile supports, comprising:
placing a support element on a roofing surface;
placing a roof tile over said support element; and
securing said roof tile to said roofing surface.

30 24. The method of installing roof tile supports of Claim 23, wherein said roofing surface comprises a roof deck.

25. The method of installing roof tile supports of Claim 23, wherein said roofing surface comprises a roof deck with battens.

26. The method of installing roof tile supports of Claim 23, wherein said roof tile is placed in contact only with said support element.

5 27. The method of installing roof tile supports of Claim 23, wherein said roof tile is placed in contact with both said roofing surface and said support element.

28. The method of installing roof tile supports of Claim 23, further including a second roof tile, wherein said first roof tile is placed in contact with said roofing surface, said support element, and said second roof tile.

10 29. The method of installing roof tile supports of Claim 23, wherein securing said roof tile to said roofing surface comprises driving a nail through said roof tile into said roofing surface.

30. The method of installing roof tile supports of Claim 29, wherein said roofing nail also passes through a portion of said support element.

15 31. The method of installing roof tile supports of Claim 23, further including a second support element, wherein said second support element is positioned to the side of said first support element so as to leave a gap between the two elements.

ROOF TILE SUPPORT

Abstract of the Disclosure

5 A roof tile support element that fits between roof tiles and a roofing surface to provide support for the roof tiles, which is compatible with a broad range of roof tiles, is adjustable during installation, and that allows individuals to walk confidently on a tile roof without breaking tiles.

10

\\DOCS_NB\FILES\DOCS\CRH\CRH-1079.DOC
100900

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205




FIG. 1




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7